



**CONCRETE SEALER** is a white milky liquid membrane curing compound. It dries clear and when applied to newly placed Pre-Krete, forms a hard moisture retaining film which retards evaporation of water, permitting better curing and higher strength. For use both indoors and outdoors and for structures.

**TECHNICAL DATA**

<b>COMPOSITION:</b>	Solution of Acrylic Polymer
<b>BOILING POINT:</b>	212°F
<b>NON-VOLATILE %:</b>	100%
<b>WT. PER GALLON:</b>	9.8 Lbs. /Gal.
<b>COVERAGE:</b>	150 - 200 square feet per gallon.
<b>DRYING RATE:</b>	Dry to touch within one hour at 70°F.
<b>SPECIFICATIONS:</b>	Meets ASTM-C-309-1, AASHO-M148-1. Formulas available to meet any state highway department specifications, an CRD-C300.
<b>PACKAGING:</b>	1 Gallon cans and 5 Gallon pails.

**APPLICATION**

Spraying is recommended. Brush or roller may be used when Pre-Krete is hard enough to prevent surface damage.

**MATERIAL SAFETY DATA SHEETS (MSDS)**

Current MSDS are available on our website: [www.pre-krete.com](http://www.pre-krete.com)

**NOTES:**